Fiscal Voor	EV 2023	Task Last Undeted.	EV 11/01/2022
PI Name:	Kharangate Chirag Ph D	Task Last Opuateu.	1111/01/2022
Project Title:	Line Chilldown and Transfer Process in Microgravity Onboard the International Space Station (ISS)		
J	C	1	
Division Name:	Physical Sciences		
Program/Discipline:			
Program/Discipline Element/Subdiscipline:	FLUID PHYSICSFluid physics		
Joint Agency Name:		TechPort:	No
Human Research Program Elements:	None		
Human Research Program Risks:	None		
Space Biology Element:	None		
Space Biology Cross-Element Discipline:	None		
Space Biology Special Category:	None		
PI Email:	chirag.kharangate@case.edu	Fax:	FY
PI Organization Type:	UNIVERSITY	Phone:	216-368-2029
Organization Name:	Case Western Reserve University		
PI Address 1:	Mechanical and Aerospace Engineering Department		
PI Address 2:	10900 Euclid Ave, Glennan 459B		
PI Web Page:			
City:	Cleveland	State:	OH
Zip Code:	44106-1712	Congressional District:	11
Comments:			
Project Type:	Ground	Solicitation / Funding Source:	2020 Physical Sciences NNH20ZDA012N: Fluid Physics. Appendix A
Start Date:	01/01/2022	End Date:	12/31/2026
No. of Post Docs:	1	No. of PhD Degrees:	
No. of PhD Candidates:	1	No. of Master' Degrees:	
No. of Master's Candidates:		No. of Bachelor's Degrees:	
No. of Bachelor's Candidates:		Monitoring Center:	NASA GRC
Contact Monitor:	Pearlman, Howard G.	Contact Phone:	216-433-4000
Contact Email:	howard.g.pearlman@nasa.gov		
Flight Program:			
Flight Assignment:			
Key Personnel Changes/Previous PI:			
COI Name (Institution):	Hartwig, Jason Ph.D. (NASA Glenn Research Center) Kassemi, Mohammad Ph.D. (Case Western Reserve University)		
Grant/Contract No.:	80NSSC22M0056		
Performance Goal No.:			
Performance Goal Text:			

Task Description:

Effective cryogenic fluid management will be important to the success of future crewed and uncrewed NASA missions. A key technological challenge in this, as recognized by NASA, is the line chilldown and transfer process. The objective of this proposal is to develop a thorough understanding of the fluid flow and thermal transport process during chilldown of transfer lines by utilizing a combination of experimental diagnostic techniques and high-fidelity computational fluid dynamics (CFD) simulations to investigate the boiling process under both terrestrial and microgravity environments. We will achieve this objective by designing a new experimental test module concept to investigate the line chilldown and transfer process that can be integrated with the Flow Boiling and Condensation Experiment (FBCE) facility onboard the International Space Station (ISS). In addition, we plan to develop a computational fluid dynamics framework for simulation of the boiling phenomena and also a reduced-order theoretical framework for the line chilldown and transfer process under terrestrial and microgravity conditions.

The proposal directly addresses the critical need in Fluid Physics for NASA's future missions where reduced-gravity multiphase flows, cryogenics, and heat transfer are identified as areas of particular interest. The research will lead to the generation of a large database of chilldown tests under terrestrial and microgravity environments, and closure theoretical and computational models to aid NASA engineers in future mission planning.

Rationale for HRP Directed Research:

In-Space Cryogenic Line Chilldown and Transfer Process: Success of NASA's future space exploration missions is dependent on cryogenic fluid management systems being able to provide safe, effective, and reliable supply of cryogenic fluid to a variety of systems.1 Two very common systems that need this supply are in-space cryogenic engines and in-space cryogenic fuel depots. A key technological challenge in this, as recognized by NASA, is the line chilldown and transfer process. In-space transfer lines during chilldown are subjected to a combination of near-saturated fluid flow with large temperature gradients as the lines are usually much warmer than the supply tanks. This leads to the occurrence of multiple transient flow boiling regimes and corresponding heat transport phenomena during the chilldown and transfer process. In the case of in-space cryogenic engines, during the initial restart of the engines, ineffective chilldown can lead to strong unwanted combustion instabilities. I Cryogenic engines lines are usually characterized by a large diameter working in short time scales. While this process is also interesting and has its challenges, it is not the focus of this project. In the project, we are interested in transfer lines specifically relating to cryogenic fuel-depots. Cryogenic fuel-depots have been planned to serve the purpose of low-Earth orbit cryogenic storage and supply to meet in-space fuel needs of customers.1 Cryogenic fuel-depot lines are usually characterized with smaller diameter pipes needing longer time scales in terms of the chilldown and transfer process. There is a need for a clear understanding of the boiling process occurring in such lines in microgravity. In addition, during chilldown of transfer lines, an ineffective boiling process can cause significant energy losses due to the possibility of unwanted evaporation and a need for venting of the cryogenic fluid mass. Therefore, effective and efficient techniques need to be developed for chilldown of the transfer process. Flow Boiling during the Line Chilldown Process: When a warmer transfer line comes in contact with a colder fluid close to its saturation temperature, the process that ensues is the transient quenching or chilldown process until the fluid flow can reach steady state. When the near saturated fluid comes in contact with the warm walls, the first step that occurs is flashing of the fluid to initiate the film boiling regime. In this domain, either a dispersed flow film boiling regime or the inverted annular flow film boiling regime is observed. As the chilldown process continues with no liquid to wall contact in this regime, the process will reach the Leidenfrost Point (LFP) before seeing an increase in heat flux in the transition boiling regime where the liquid starts to rewet the heated surface. This increase in heat flux continues until the critical heat flux point (CHF) is reached, where complete liquid is in contact with the wall followed by transition to the nucleate boiling regime. The heat flux then continues to drop until all the vapor is extinguished and the single-phase forced convection domain is reached, ending the chilldown process. Gaps in Line Chilldown and Transfer Process Research: The accurate capture and prediction of this heat flux vs. wall temperature difference data in microgravity for the complete quenching curve is a big motivation for conducting line chilldown experiments on the ISS. The past 60 years have seen numerous researchers trying to understand this phenomenon experimentally, mostly in terrestrial environments with a few experiments conducted under reduced gravity conditions. In a recent study, Darr et al. summarized a list of all available worldwide databases investigating quenching using cryogenic fluids. These studies could have served the basis for a thorough understanding on this phenomenon in 1-g and to some extent in reduced gravity. However, most of them include data that are deemed unusable due to missing information on rebuilding the full quenching curve, including missing data on either the temperature as a function of time, the pressure as a function of time, the mass flux, the inlet state, and/or the wall and parasitic heat fluxes. The remaining data including the two common fluids with usable data are Liquid Hydrogen (LH2) and Liquid Nitrogen (LN2). There are 12,137 datapoints for LH2 tested in vertical upflow configuration. In addition, there are 62,917 datapoints for LN2 tested in various orientations with respect to Earth gravity and another 4,211 datapoints under reduced gravity conditions of 2*10-2g. In other studies, quenching tests of transfer lines under reduced gravity have been performed with non-cryogenic fluids, including R113 tested by Westbye et al. and Kawaji et al., and Freon-113 by Adham-Khodaparast et al., all onboard the NASA KC-135 flight. Celata et al. also performed quenching experiments with FC-72 as the working fluids onboard a Zero-G flight, which is a modified Airbus-300. While the issue of non-reporting of all the necessary information to recreate the quenching curve makes their data also unusable for further analysis and investigation, but also important to note is none of their data is under pure microgravity conditions. We can see four major gaps in the available literature for accurately understanding and predicting the line chilldown and transfer quench process in microgravity environments, and thus, developing good modeling and/or computational predicting tools: (1) Non-availability of data under pure, sustained microgravity environments. (2) Majority of the usable data is in the high liquid Reynolds number region with Ref > 20,000, which can limit developing a fundamental understanding of flow boiling behaviors that can be better investigated starting at slow or laminar flows. (3) Low availability of overall datapoints covering large geometric variations. (4) Not much published data on varying inlet flows conditions including pulse flows that can be highly effective for cryogenic chilldown and transfer processes for the proposed fuel-depot application. Objectives of the current project: The discussion above clearly demonstrates the gaps in today's research on the line chilldown and transfer process. In this project, we plan to address the major limitations by an integrated experimental and numerical approach, which combines the strengths of both techniques, to develop a thorough understanding of the fluid flow and thermal transport under terrestrial and microgravity environments. The availability of the FBCE facility onboard the ISS with normal perfluorohexane (C6F14 or nPFH) as the working fluid will help us investigate the flow boiling during quenching inside a tube in detail under sustained, long-duration microgravity, and the data will help us develop the computational framework and a theoretical model to predict the boiling behavior accurately.

Research Impact/Earth Benefits:

	The annual progress of the present research on "Line Chilldown and Transfer Process in Microgravity Onboard the International Space Station (ISS)" can be summarized in three parts as follows: Development and Testing of a Two-Phase Flow Chill-down Test Module for Integration with the FBCE Module at ISS:	
	The new experimental test concept for the two-phase chilldown tests has been tested in the flow conditioning loop at Case Western Reserve University (CWRU), which is very similar to the actual Flow Boiling and Condensation Experiments (FBCE) module onboard the ISS. This will ensure that the new flow boiling module can replace the current module in the FBCE which will fit in the existing space and can be utilized to obtain both terrestrial and long-duration microgravity data for the line chilldown and transfer process. The main technological challenge for the new design is the pre-heating phase, where the test section walls should be heated to the desired temperature before starting the chilldown tests. The use of a simple check valve near the test section outlet along with a charged accumulator in the flow loop resolved this issue. Also, it has been experimentally shown that the fluid temperature is always at saturation vapor conditions, never superheated, after the heated test section due to the continuous presence of some liquid in the test section, which eliminates the need for additional cooling of the fluid before entering the FBCE loop. Initial chilldown data for a 3/8'' stainless steel tube is now available with the new experimental concept which will be further extended for the entire test matrix conditions. The transparent Pyrex test section for the flow visualization test section during the chilldown process is also ready and will be tested by the end of this year.	
Task Progress:	CFD Studies on Liquid Nitrogen Flow Boiling During the Cryogenic Transfer Line Chill-down Process:	
	The prediction of the transfer line chill-down curve possesses unique challenges due to the presence of different flow boiling regimes, viz. film, transition and nucleate boiling; and hence, implementing a single computational fluid dynamics (CFD) modeling approach may not be adequate. Initial validations for the film boiling using a 3D mixture model for the liquid nitrogen chilldown data available in the literature is in a matured phase and will be applied for other operating conditions for robust predictions. A user-defined function in Fluent for predicting transition and nucleate boiling is in the development phase and will be implemented along with the 3D mixture model to predict the entire chilldown curve.	
	Development of a 1-D Theoretical Model for Line Chill-down Process:	
	A 1-D MATLAB code has been developed based on the published literature and has been tested for the different test matrix conditions for both stainless steel and Pyrex. This helped in fixing the limits for different flow and operating parameters in the test matrix and will be further refined based on the chilldown test data from the present project.	
	In addition, the Science Requirements Document (SRD) for the project is being completed and is progressing in collaboration with the University of Illinois, Urbana-Champaign (UIUC), and is due in January, 2023.	
Bibliography Type:	Description: (Last Updated: 11/26/2024)	
Abstracts for Journals and Proceedings	Narayanan JK, Shingote C, Huang C-N, Pirnstill L, Kassemi M, Hartwig JW, Mackey JR, Pearlman HG, Kharangate CR. "Development and testing of a two-phase flow chill-down test module for integration with the Flow Boiling and Condensation Experiments at ISS." 38th Annual Meeting of the American Society for Gravitational and Space Research, Houston, TX, November 9-12, 2022. Abstracts. 38th Annual Meeting of the American Society for Gravitational and Space Research, Houston, TX, November 9-12, 2022.	
Articles in Peer-reviewed Journals	Liu B, Goree J, Pustylnik MY, Thomas HM, Fortov VE, Lipaev AM. "Time-dependent shear motion in a strongly coupled dusty plasma in PK-4 on the International Space Station (ISS)." IEEE Transactions on Plasma Science. 2021 Sep;49(9):2972-8. http://dx.doi.org/10.1109/TPS.2021.3100300, Sep-2021	