Task Book Report Generated on: 05/03/2024

Fiscal Year:	FY 2024	Task Last Updated:	FV 09/26/2023
PI Name:	Stirling, Leia Ph.D.	rask East Opuateu.	11 07/20/2023
Project Title:	HCAAM VNSCOR: Responsive Multimodal Human-Automation Communication for Augmenting Human Situation Awareness in Nominal and Off-Nominal Scenarios (80NSSC20K0409)		
Division Name:	Human Research		
Program/Discipline:			
Program/Discipline Element/Subdiscipline:			
Joint Agency Name:		TechPort:	No
<b>Human Research Program Elements:</b>	(1) HFBP:Human Factors & Behavioral Performance (IRP Rev H)		
Human Research Program Risks:	None		
Space Biology Element:	None		
Space Biology Cross-Element Discipline:	None		
Space Biology Special Category:	None		
PI Email:	leias@umich.edu	Fax:	FY
PI Organization Type:	UNIVERSITY	Phone:	617-324-7410
Organization Name:	University of Michigan		
PI Address 1:	Industrial and Operations Engineering		
PI Address 2:	1205 Beal Avenue, G634 IOE Building		
PI Web Page:			
City:	Ann Arbor	State:	MI
Zip Code:	48109	<b>Congressional District:</b>	12
Comments:	NOTE: PI moved to University of	Michigan in fall 2019; previous aff	filiation was Massachusetts Institute of Technology
Project Type:	GROUND		2017-2018 HERO 80JSC017N0001-BPBA Topics in Biological, Physiological, and Behavioral Adaptations to Spaceflight. Appendix C
Start Date:	12/04/2019	End Date:	12/03/2024
No. of Post Docs:	0	No. of PhD Degrees:	0
No. of PhD Candidates:	4	No. of Master' Degrees:	0
No. of Master's Candidates:	0	No. of Bachelor's Degrees:	1
No. of Bachelor's Candidates:	2	Monitoring Center:	NASA JSC
Contact Monitor:	Whitmire, Alexandra	Contact Phone:	
Contact Email:	alexandra.m.whitmire@nasa.gov		
Flight Program:			
Flight Assignment:	NOTE: End date changed to 12/0.	3/2024 per NSSC information (Ed.,	11/10/23).
Key Personnel Changes/Previous PI:	N/A		
COI Name (Institution):	Blossom, Jonathon ( NASA Jet Propulsion Laboratory ) Atkins, Ella Ph.D. ( Virginia Tech ) Liu, Andrew Ph.D. ( Massachusetts Institute of Technology )		
Grant/Contract No.:	80NSSC20K0409		
Performance Goal No.:			
Performance Goal Text:			

Task Book Report Generated on: 05/03/2024

[Ed. note April 2020: Continuation of "HCAAM VNSCOR: Responsive Multimodal Human-Automation Communication for Augmenting Human Situation Awareness in Nominal and Off-Nominal Scenarios," grant 80NSSC19K0703, with the same Principal Investigator (PI) Leia Stirling, Ph.D., due to PI move to University of Michigan from Massachusetts Institute of Technology in fall 2019]

This task is part of the Human Capabilities Assessments for Autonomous Missions (HCAAM) Virtual NASA Specialized Center of Research (VNSCOR).

Crew extravehicular activity (EVA) is limited on spaceflight missions. Multiple, small robotic spacecraft with varying levels of autonomy are needed to perform tasks that might have been completed by an astronaut (e.g., an exterior surface inspection or repair). Crews on long duration exploration missions (LDEM) will have less access to ground support during task operations. As a result, they will need to process more information and communicate with autonomous robots effectively to ensure tasks are progressing safely and on schedule.

The objective of these studies is to investigate the use of augmented reality (AR) multimodal interface displays and communication pathways for improving human-robot communication, situation awareness (SA), trust, and task performance. This will lead to developing guidelines for designing human-robot system interactions that enable operational performance for crews on spaceflight missions.

The specific aims are to:

- 1) Develop a simulation testbed for examining communication between human-robot teams.
- 2) Develop a hardware testbed for examining communication between human-robot teams.
- 3) Evaluate human SA, trust, and task performance within a short duration and long-duration ground-based study (simulation and/or hardware) through testing various interface communication modalities and information displays.
- 4) (Option) Perform additional studies for alternate parameters of interest that could be tested using the study testbeds. Additional parameters include timing and persistence of information, gesture command mapping, varying the levels of robot automation, evaluating precision enabled by each command mode.

## Rationale for HRP Directed Research:

Research Impact/Earth Benefits:

**Task Description:** 

Augmented Reality (AR) has the opportunity to support decision making across a variety of use-case scenarios, including but not limited to manufacturing, automated vehicles, military training, and entertainment. This research compares AR to other visual modalities for telerobotics applications, specifically considering robotic control and anomaly inspection. Results from this study can inform how AR is integrated for task-specific applications, as there may be tasks that have increased benefit from AR, whereas others may have additional considerations that emerge.

The objective of these studies is to investigate the use of augmented reality (AR) multimodal interface displays and communication pathways for improving human-robot communication, situation awareness (SA), trust, and task performance. This will lead to developing guidelines for designing human-robot system interactions that enable operational performance for crews on spaceflight missions.

During this reporting period, our team supported the NASA Human Exploration Research Analog (HERA) Campaign 6 missions in data collection and performed data analysis for the missions completed. This study used the Unity-based simulation testbed developed in an earlier year of the program for evaluating the aims of assessing visual presentation modality across two tasks. The visual modalities considered were: (1) 2D camera images from fixed cameras placed externally on a simulated space station, (2) 3D reconstruction shown on a 2D projection, and (3) 3D reconstruction shown in an Augmented Reality environment using the HoloLens v2 platform. The reconstruction simulates using 2D camera images from the inspector to create the 3D object. The tasks evaluated were Synchronous and Asynchronous inspection task. In the Synchronous task, participants flew an inspector robot around the spacecraft to identify any surface anomalies that required closer inspection. The inspector could be flown in automatic mode along a predetermined path or manual mode to move off the assigned path. The robot was controlled with a 3-DOF joystick. In the Asynchronous task, participants analyzed the imagery from a previous inspection flight to identify the potential anomalies on the spacecraft exterior. In both tasks, detected anomalies were captured by taking a picture of the anomaly within the viewpoint. Initial HERA results support that detection accuracy was the highest for the 2D display for the Synchronous Inspection task. Additional interactive 3D viewpoints decreased detection accuracy and increased task completion time. Augmented Reality provided no significant improvement to local navigation, i.e., minimum distance to station or portion of time within two meters, suggesting that the technology did not enhance the perception level of situation awareness. Based on these findings, mission planning operations, when applicable, should include synchronous human-in-the-loop presence for telerobotic inspection of spacecraft. Additional details on the single session study are available in Weiss et al. (2021) and on the initial HERA findings in Liu et al. (2022).

During the reporting period, our team also performed studies to support gaps in the NASA Human Integration Design Handbook (HIDH) for augmented reality (AR) interfaces. We compared performance on sensorimotor and neurovestibular assessment tasks using physical objects and within AR. The sensorimotor task was a multi-directional Fitts' Law target acquisition task, while the neurovestibular tasks included three clinical balance assessments (Four Square Step test (FSST), the Star Excursion, tandem walking (TW)), and three operational tasks (capsule ingress and egress, geology sampling, and obstacle avoidance). For the sensorimotor task, the touchscreen modality yielded improved performance over AR as measured by accuracy, precision, error rates, throughput, and movement time. AR designers can improve performance when designing AR interfaces by selecting larger buttons when accuracy and efficiency are required and by embedding perception cues to button target surfaces such as depth and proximity cues. For the neurovestibular tasks, while participants were able to perform all assessment tasks successfully, their strategies differed when comparing AR performance to physical object use. Task completion times were longer when administered in AR. Preliminary results yielded higher step heights in the TW, FSST, and capsule egress task as well as higher foot placement variability in the FSST. To maintain head stability for viewing the holographic content within the TW task, participants restricted their torso movement. While performing the capsule egress task, the AR and physical objects differed significantly in the downward pitch of the head, but not the torso. The participants were able to complete all tasks within AR and meaningful measures of task performance and postural control were obtained, indicating that AR may be a useful instrumentation solution with embedded sensors to evaluate task performance and postural control.

Task Progress:

Task Book Report Generated on: 05/03/2024

	However, care should be taken when comparing performance within AR to other assessment modalities. Results from these studies support research gaps identified in NASA's Human Research Roadmaps, provide design guidance for AR in NASA's Human Integration Design Handbook, and support determining whether AR is a viable tool for evaluating astronauts' vestibular performance throughout mission timelines.
Bibliography Type:	Description: (Last Updated: 11/09/2023)
Articles in Peer-reviewed Journals	Weiss H, Liu A, Byon A, Blossom J, Stirling L. "Comparison of display modality and human-in-the-loop presence for on-orbit inspection of spacecraft." Hum Factors. 2023 Sep;65(6):1059-73. <a href="https://doi.org/10.1177/00187208211042782">https://doi.org/10.1177/00187208211042782</a> ; PubMed <a href="https://doi.org/10.1177/00187208211042782">PMID: 34558994</a> , Sep-2023
Articles in Peer-reviewed Journals	Larson H, Stirling L. "Examination of human spatial reasoning capability and simulated autonomous rendezvous and docking monitoring performance." Proc Hum Factors Ergon Soc Annu Meet. Oct 25;21695067231192262. <a href="https://doi.org/10.1177/2169506723119226">https://doi.org/10.1177/2169506723119226</a> , Oct-2023
Papers from Meeting Proceedings	Weiss H, Stirling L. "Usability Evaluation of an Augmented Reality Sensorimotor Assessment Tool for Astronauts." IEEE Aerospace Conference, Big Sky, Montana, March 4-11, 2023. IEEE Aerospace Conference, Big Sky, Montana, March 4-11, 2023. , Mar-2023
Papers from Meeting Proceedings	Tang J, Weiss H, Stirling L. "A Comparison of Sensorimotor Assessment Accuracy between Augmented Reality and Touchscreen Environments." 67th International Annual Meeting of the Human Factors and Ergonomics Society, Washington, District of Columbia, October 23-27, 2023. 67th International Annual Meeting of the Human Factors and Ergonomics Society, Washington, District of Columbia, October 23-27, 2023., Oct-2023
Papers from Meeting Proceedings	Larson H, Stirling L. "Examination of Human Spatial Reasoning Capability and Simulated Autonomous Rendezvous and Docking Monitoring Performance." 67th International Annual Meeting of the Human Factors and Ergonomics Society, Washington, District of Columbia, October 23-27, 2023. 67th International Annual Meeting of the Human Factors and Ergonomics Society, Washington, District of Columbia, October 23-27, 2023., Oct-2023